



Information Sheet: IS/80

THE USER'S GUIDE TO PROTIM E406 PRESERVED WOOD

What is Protim E406 Preserved Wood ?

Protim E406* preserved wood has been preserved by the correct application of Protim E406 wood preservative and then allowed to dry.

Properly treated Protim E406 preserved wood is protected against attack by wood decaying fungi and wood destroying insects.

Protim E406 preserved wood is suitable for internal and external applications which are out of ground contact and above the damp-proof course, including doors, window frames, surrounds and frames.

Timbers exposed to weathering must be given the additional protection of a durable and well maintained surface finish.

IMPORTANT INFORMATION

Wear gloves when working with wood. Wear a dust mask and goggles when cutting or sanding wood. Wash work clothes separately from other household clothing before re-use.

Only preserved wood that is visibly clean and free of surface residue should be used.

Some preservative may migrate from the treated wood into soil/water or may dislodge from the treated wood surface upon contact with skin. Wash exposed skin areas thoroughly.

Treated timber should be stored internally, or undercover, before installation. It should not be exposed to constant or significant rainfall, nor allowed to rest in standing water. If wood is to be used in an interior application and becomes temporarily wetted during construction, it should be allowed to dry before being covered or enclosed.

Mould growth can and does occur on the surface of many products, including treated or untreated wood, during prolonged surface exposure to excessive moisture conditions. To remove mould from treated wood surfaces, wood should be allowed to dry. Typically, mild soap and water can be used to remove remaining surface mould.

Preserved wood should not be used where it may come into direct or indirect contact with drinking water.

Do not use preserved wood under circumstances where the preservative may become a component of food, animal feed or beehives.

Do not use preserved wood as mulch.

Do not burn preserved wood (see Disposal). All sawdust and construction debris should be cleaned up and disposed of after construction.

Effective Use of Preserved Wood

Cutting

Preserved wood should not be cut or otherwise reworked as this will expose unpreserved wood.

Any surface exposed by drilling or cutting must be re-treated with an approved (i.e. by the UK Health and Safety Executive) cut end preservative. Failure to re-treat may reduce the effectiveness of the preservative treatment. Rip-sawing, thicknessing and planing are not permitted unless the timber is subsequently re-preserved to the original specification.

If cutting cannot be avoided, then precautions should be taken to keep airborne dust levels below the Workplace Exposure Limit for Wood Dust. In particular, avoid inhalation of dust when using high speed cross-cut saws or mechanical sanders.

Metal Fastenings and Hardware

Certain metal products (including fasteners, hardware and flashing) may corrode when in direct contact with wood exposed to water. Use fixings and other hardware which are in compliance with building regulations for the intended use. Use fixings, hardware or any metal products as recommended by their manufacturer.

Protim E406 can be used in close association with bituminous felts.

Finishing

The compatibility of glues and mastics should be checked before application. Always follow the product manufacturer's recommendations.



If you desire to apply a paint, stain, clear water repellent or other finish to your preservative treated wood, we recommend that you apply the finishing product to a small test area to ensure that it provides the intended result, before proceeding.

Disposal

Do not burn preserved wood. All sawdust and construction debris should be cleaned up and disposed of after construction. Protim E406 preserved timbers which are no longer usable, such as cut ends, broken boards, sawdust, or preserved timber material taken out of service, may be disposed of in landfills or burned in commercial or industrial incinerators or boilers in accordance with national and local regulations. Do not allow wood waste which contains preservative to be used for animal litter.

Biocidal Product Regulation (EU 528/2012) Article 58 Information

Protim E406 preserved wood is a "treated article" which incorporates biocidal products. Wood correctly preserved with Protim E406 is protected against wood destroying insects and wood rotting fungi.

Contains: Permethrin, Propiconazole, Tebuconazole.

ADDITIONAL INFORMATION

Protim E406 preserved wood products are produced by independently owned and operated wood preserving facilities. Koppers Performance Chemicals provides a range of products and technologies for the treatment, protection and enhancement of timber. Information and advice is available on all aspects of our products from the Technical Services Department.

For more information visit www.kopperspc.eu

Or contact: kpc@koppers.eu
Telephone: +44 (0) 1628 486644
Emergency: +44 (0) 1628 890907

* Protim is a registered trademarks of Protim Solignum Ltd.

IS/80 © December 2015

Protim Solignum Ltd
Fieldhouse Lane, Marlow, Bucks SL7 1LS, UK | Tel: 00 44 (0)1628 486644 | Fax: 00 44 (0)1628 476757
Registered in England - 3037845 | Registered Office: Fieldhouse Lane, Marlow, Bucks SL7 1LS UK

Protim Solignum Limited's products are sold subject to its standard Terms and Conditions of Sale, copies of which may be obtained on request. Whilst Protim Solignum endeavours to ensure that any advice, recommendation, specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification, recommendation or information given by it save as specifically provided by its Terms and Conditions of Sale.